

<u>Code</u>	<u>Omschrijving</u>	
1511901910, 1511909110, 1513111010, 1513193010, 1513211010, 1513293010	Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: — industrial monocarboxylic fatty acids of subheading 3823 19 10, — methyl esters of fatty acids of heading 2915 or 2916, — fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products, — fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products, — stearic acid of subheading 3823 11 00 — goods of heading 3401 or — fatty acids with high purity of heading 2915 for the manufacture of chemical products other than products of heading 3826 (1)#####	Ter bespreking
2008994894	Mango puree: — not from concentrate, — of the genus Mangifera, — of a Brix value of 14 or more, but not more than 20 used in the manufacture of products of drink industry# (1)	Automatisch
2009419220, 2009419970	Pineapple juice: — not from concentrate, — of the genus Ananas, — of a Brix value of 11 or more but not more than 16, used in the manufacture of products of drink industry# (1)#	Automatisch
2805309045, 2805309055, 2805309065	Rare-earth metals, scandium and yttrium, of a purity by weight of 95 % or more##	Automatisch
2818109110	Sintered corundum with micro crystalline structure, containing by weight: — 94 % or more, but not more than 98,5 % of α -Al ₂ O ₃ (CAS RN 1344-28-1), — 2 % (\pm 1,5 %) of magnesium spinel (CAS RN 1309-48-4), — 1 % (\pm 0,6 %) of yttrium oxide (CAS RN 1314-36-9), and — either 2 % (\pm 1,2 %) of lanthanum oxide (CAS RN 1312-81-8) — or 2 % (\pm 1,2 %) of lanthanum oxide (CAS RN 1312-81-8) and neodymium oxide (CAS RN 1313-97-9) with less than 50 % of the total weight having a particle size of more than 10 mm	Automatisch
2826199010	Tungsten hexafluoride with a purity of 99,9 % by weight or more (CAS RN 7783-82-6)	Automatisch
2833298030	Zirconium sulphate (CAS RN 14644-61-2)	Automatisch
2846100040	Cerium lanthanum neodymium praseodymium carbonate, whether or not hydrated	to be deleted
2903999070	$\alpha,\alpha,\alpha',\alpha'$ -Tetrachloro-o-xylene (CAS RN 25641-99-0)	Niet automatisch
2904200010	Nitromethane (CAS RN 75-52-5)	Automatisch
2904200020	Nitroethane (CAS RN 79-24-3)	Automatisch
2904200030	1-Nitropropane (CAS RN 108-03-2)	Automatisch

2905299010	3,5-Dimethylhex-1-yn-3-ol (CAS RN 107-54-0)	to be deleted
2905299030	Dodeca-8,10-dien-1-ol (CAS RN 33956-49-9)	Niet automatisch
2905399510	Propane-1,3-diol (CAS RN 504-63-2)	Automatisch
2909309030	3,4,5-Trimethoxytoluene (CAS RN 6443-69-2)	Automatisch
2909500020	Ubiquinol (CAS RN 992-78-9)	Automatisch
2912490030	Salicylaldehyde (CAS RN 90-02-8)	Automatisch
2914290030	(R)-p-Mentha-1(6),8-dien-2-one (CAS RN 6485-40-1)	Automatisch
2914500020	3'-Hydroxyacetophenone (CAS RN 121-71-1)	Automatisch
2914700060	4'-tert-Butyl-2',6'-dimethyl-3',5'-dinitroacetophenone (CAS RN 81-14-1)	Automatisch
2915390060	Dodec-8-enyl acetate (CAS RN 28079-04-1)	Automatisch
2915390065	Dodeca-7,9-dienyl acetate (CAS RN 54364-62-4)	Automatisch
2915390070	Dodec-9-enyl acetate (CAS RN 16974-11-1)	Automatisch
2915907060	Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0)	Automatisch
2916130010	Hydroxyzinc methacrylate powder (CAS RN 63451-47-8)	Automatisch
2916200060	3-Cyclohexylpropionic acid (CAS RN 701-97-3)	Automatisch
2916399025	2-Methyl-3-(4-Fluorophenyl)-propionyl chloride (CAS RN 1017183-70-8)	Niet automatisch
2916399030	2,4,6-Trimethylbenzoyl chloride (CAS RN 938-18-1)	Automatisch
2917199050	Tetradecanedioic acid (CAS RN 821-38-5)	Automatisch
2917399520	Dibutyl-1,4-benzenedicarboxylate (CAS RN 1962-75-0)	Automatisch
2917399530	Benzene-1,2:4,5-tetracarboxylic dianhydride (CAS RN 89-32-7)	Automatisch
2920908520	Tris(methylphenyl)phosphite (CAS RN 25586-42-9)	Automatisch
2920908530	2,2'-[[3,3',5,5'-Tetrakis(1,1-dimethylethyl)[1,1'-biphenyl]-2,2'-diyl]bis(oxy)]bis[biphenyl-1,3,2-dioxaphosphepine], (CAS RN 138776-88-2)	Automatisch
2920908540	Bis(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8)	Automatisch
2921290040	Decamethylenediamine (CAS RN 646-25-3)	Automatisch
2921309930	1,3-Cyclohexanedimethanamine (CAS RN 2579-20-6)	Automatisch
2921420082	2-Chloro-4-nitroaniline (CAS RN 121-87-9)	Niet automatisch
2921430050	4-Aminobenzotrifluoride (CAS RN 455-14-1)	Automatisch

2921430060	3-Aminobenzotrifluoride (CAS RN 98-16-8)	Automatisch
2921450010	Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate (CAS RN 4681-22-5)	to be deleted
2921490080	4-Heptafluoroisopropyl-2-methylaniline (CAS RN 238098-26-5)	Automatisch
2922290075	4-(2-Aminoethyl)phenol (CAS RN 51-67-2)	Automatisch
2922390020	2-Amino-5-chlorobenzophenone (CAS RN 719-59-5)	Automatisch
2922498545	Glycine (CAS RN 56-40-6)	Automatisch
2923900075	Tetraethylammonium hydroxide, in the form of an aqueous solution containing: — 35 % (\pm 0,5 %) by weight of tetraethylammonium hydroxide, — not more than 1 000 mg/kg of chloride, — not more than 2 mg/kg of iron and — not more than 10 mg/kg of potassium	Automatisch
2924299840	N,N'-1,4-Phenylenebis[3-oxobutyramide], (CAS RN 24731-73-5)	Automatisch
2924299845	Propoxur (ISO) (CAS RN 114-26-1)	Automatisch
2924299850	N,N'-(2,5-Dichloro-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 42487-09-2)	Niet automatisch
2924299855	N,N'-(2,5-Dimethyl-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 24304-50-5)	Automatisch
2924299860	N,N'-(2-Chloro-5-methyl-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 41131-65-1)	Automatisch
2926909530	2-Amino-3-(3,4-dimethoxyphenyl)-2-methylpropanenitrile hydrochloride, (CAS RN 2544-13-0)	Niet automatisch
2926909563	1-(Cyanoacetyl)-3-ethylurea (CAS RN 41078-06-2)	to be deleted
2928009025	Acetaldehyde oxime in an aqueous solution (CAS RN 107-29-9)	Automatisch
2929100055	2,5 (and 2,6)-Bis(isocyanatomethyl)bicyclo[2.2.1]heptane (CAS RN 74091-64-8)	Niet automatisch
2930909910	2,3-Bis((2-mercaptoethyl)thio)-1-propanethiol (CAS RN 131538-00-6)	Automatisch
2930909920	2-Methoxy-N-[2-nitro-5-(phenylthio)phenyl]acetamide (CAS RN 63470-85-9)	Niet automatisch
2930909950	[S-(R*,R*)]-2-Amino-1-[4-(methylthio)-phenyl]-1,3-propanediol, (CAS RN 23150-35-8)	Niet automatisch
2930909955	Thiourea (CAS RN 62-56-6)	Automatisch
2930909965	Pentaerythritol tetrakis(3-mercaptopropionate) (CAS RN 7575-23-7)	Niet automatisch
2931908005	Diethylmethoxyborane (CAS RN 7397-46-8), whether or not in the form of a solution in tetrahydrofuran according to note 1e to Chapter 29 of the CN	Automatisch
2931908010	Triethylborane (CAS RN 97-94-9)	Niet automatisch
2931908020	Diethylborane isopropoxide (CAS RN 74953-03-0)	Niet automatisch

2932190050	2-Methylfuran (CAS RN 534-22-5)	Niet automatisch
2932990050	7-Methyl-3,4-dihydro-2H-1,5-benzodioxepin-3-one (CAS RN 28940-11-6)	Automatisch
2933210080	5,5-Dimethylhydantoin (CAS RN 77-71-4)	Automatisch
2933399920	Copper pyrithione powder (CAS RN 14915-37-8)	Automatisch
2933399947	(-)-trans-4-(4'-Fluorophenyl)-3-hydroxymethyl-N-methylpiperidine (CAS RN 105812-81-5)	to be deleted
2933399949	2-[[[3-Methyl-4-(2,2,2-trifluoroethoxy)-2-pyridinyl]methyl]thio]-1H-benzimidazole, (CAS RN 103577-40-8)	Niet automatisch
2933399985	2-Chloro-5-chloromethylpyridine (CAS RN 70258-18-3)	Automatisch
2933499030	Quinoline (CAS RN 91-22-5)	Automatisch
2933499040	Isoquinoline (CAS RN 119-65-3)	Automatisch
2933698055	Terbutryn (ISO) (CAS RN 886-50-0)	Automatisch
2933698060	Cyanuric acid (CAS RN 108-80-5)	Automatisch
2933790070	(S)-N-[(Diethylamino)methyl]-alpha-ethyl-2-oxo-1-pyrrolidineacetamide L-(+)-tartrate, (CAS RN 754186-36-2)	Automatisch
2933998064	((3R)-1-{(1R,2R)-2-[2-(3,4-Dimethoxyphenyl) ethoxy]cyclohexyl}pyrrolidin-3-ol.hydrochloride, (CAS RN 748810-28-8)	Niet automatisch
2934208060	Benzothiazol-2-yl-(Z)-2-trityloxyimino-2-(2-aminothiazole-4-yl)-thioacetate (CAS RN 143183-03-3)	Automatisch
2934208070	N,N-Bis(1,3-benzothiazol-2-ylsulphanyl)-2-methylpropan-2-amine (CAS RN 3741-80-8)	Automatisch
2934999025	2,4-Diethyl-9H-thioxanthen-9-one (CAS RN 82799-44-8)	Automatisch
2934999040	2-Thiophene ethylamine (CAS RN 30433-91-1)	Niet automatisch
2934999050	10-[1,1'-Biphenyl]-4-yl-2-(1-methylethyl)-9-oxo-9H-thioxanthenium hexafluorophosphate, (CAS RN 591773-92-1)	Automatisch
2934999085	N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluoroacetyl-L-lysyl-N2-carboxy anhydride (CAS RN 126586-91-2)	Niet automatisch
2934999086	Dithianon (ISO) (CAS RN 3347-22-6)	Automatisch
2934999087	2,2'-(1,4-Phenylene)bis(4H-3,1-benzoxazin-4-one) (CAS RN 18600-59-4)	Automatisch
2935009030	Mixture of isomers consisting of N-ethyltoluene-2-sulphonamide and N-ethyltoluene-4-sulphonamide	to be deleted
2935009040	Imazosulfuron (ISO), of a purity by weight of 98 % or more (CAS RN 122548-33-8)	Niet automatisch
2935009042	Penoxsulam (ISO) (CAS RN 219714-96-2)	Automatisch

2938903010	Ammonium glycyrrhizate (CAS RN 53956-04-0)	Automatisch
3204110020	Colourant C.I. Disperse Yellow 241 (CAS RN 83249-52-9) and preparations based thereon with a colourant C.I. Disperse Yellow 241 content of 97 % or more by weight	Automatisch
3204110030	Preparation of dispersion dyes, containing: — C.I. Disperse Orange 61, — C.I. Disperse Blue 291:1, — C.I. Disperse Violet 93:1, — C.I. Disperse Red 54	Automatisch
3204190011	Photochromic dye, 3-(4-butoxyphenyl-6,7-dimethoxy-3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-11-carbonitrile	to be deleted
3204190031	Photochromic dye, N-hexyl -6,7-dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-11-carboxamide	to be deleted
3204190041	Photochromic dye, 4,4'-(13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-3,3-diyl)diphenol	to be deleted
3204190051	Photochromic dye, 4-(4-(6,11-difluoro-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl)phenyl)morpholine (CAS RN 1360882-72-6)	to be deleted
3204190071	Colourant C.I. Solvent Brown 53 (CAS RN 64696-98-6) and preparations based thereon with a colourant C.I. Solvent Brown 53 content of 95 % or more by weight	Automatisch
3204190073	Colourant C.I. Solvent Blue 104 (CAS RN 116-75-6) and preparations based thereon with a colourant C.I. Solvent Blue 104 content of 97 % or more by weight	Automatisch
3215900040	Dry ink powder with a base of hybrid resin (made from polystyrene acrylic resin and polyester resin) mixed with: — wax; — a vinyl-based polymer and — a colouring agent for use in the manufacture of toner bottles for photocopiers, fax machines, printers and multifunction devices# (1)	Automatisch
3402119010	Sodium lauroyl methyl isethionate	Automatisch
3402901030	Surface-active preparation, consisting of a mixture of sodium docusate and ethoxylated 2,4,7,9-tetramethyldec-5-yne-4,7-diol (CAS RN 577-11-7 and 9014-85-1)	Automatisch
3402901050	Surface-active preparation, consisting of a mixture of polysiloxane and poly(ethylene glycol)	Automatisch
3402901060	Surface-active preparation, containing 2-ethylhexyloxymethyl oxirane	Automatisch
3707909080	Anti-reflection coating, consisting of either a siloxane polymer or an organic polymer having a phenolic hydroxy group modified with a chromophore group, in the form of a solution of an organic solvent containing either 1-ethoxy-2-propanol or 2-methoxy-1-methylethyl acetate containing by weight not more than 10 % of polymer	Automatisch

3808939020	Preparation consisting of benzyl(purin-6-yl)amine in a glycol solution, containing by weight: — 1,88 % or more but not more than 2,00 % of benzyl(purin-6-yl)amine of a kind used in plant growth regulators	Automatisch
3808939030	Aqueous solution containing by weight: — 1,8 % of sodium para-nitrophenolate, — 1,2 % of sodium ortho-nitrophenolate, — 0,6 % of sodium 5-nitroguaiacolate for use in the manufacture of a plant growth regulator # (1)	Automatisch
3808939040	Mixed white powder containing by weight: — 3 % or more but not more than 3,6 % of 1-methylcyclopropene with a purity more than 96 % and — containing less than 0,05 % of each impurity of 1-chloro-2-methylpropene and 3-chloro-2-methylpropene for use in the manufacture of a growth regulator of post-harvest fruits, vegetables and ornamentals with a specific generator# (1)	Automatisch
3808939050	Preparation in the form of powder, containing by weight: — 55 % or more of Gibberellin A4, — 1 % or more but not more than 35 % of Gibberellin A7, — 90 % or more of Gibberellin A4 and Gibberellin A7 combined — not more than 10 % of a combination of water and other naturally occurring Gibberellins of a kind used in plant growth regulators	Automatisch
3808999010	Oxamyl (ISO) (CAS RN 23135-22-0) in a solution of cyclohexanone and water	Automatisch
3815909030	Catalyst, consisting of a suspension in mineral oil of: — tetrahydrofuran complexes of magnesium chloride and titanium(III) chloride; and — silicon dioxide — containing 6,6 % (\pm 0,6 %) by weight of magnesium, and — containing 2,3 % (\pm 0,2 %) by weight of titanium	Automatisch
3815909080	Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol	Automatisch
3824909240	Mixture containing two or three of the following acrylates: — urethane acrylates, — tripropylene glycoldiacrylate, — ethoxylated bisphenol A acrylate and — poly(ethyleneglycol) 400 diacrylate	to be deleted
3824909241	Solution of (chloromethyl)bis(4-fluorophenyl)methylsilane of a nominal concentration of 65 % in toluene	Niet automatisch
3824909243	Preparation, consisting of a mixture of 2,4,7,9-tetramethyldec-5-yne-4,7-diol and propan-2-ol	Niet automatisch
3824909244	Preparation containing by weight: — 85 % or more but not more than 95 % of α -4-(2-cyano-2-butoxycarbonyl)vinyl-2-methoxy-phenyl- ω -hydroxyhexa(oxyethylene), and — 5 % or more but not more than 15 % of polyoxyethylene (20) sorbitan monopalmitate	Automatisch

3824909246	Diethylmethoxyborane (CAS RN 7397-46-8) in the form of a solution in tetrahydrofuran	Automatisch
3824909254	Poly(tetramethylene glycol) bis[(9-oxo-9H-thioxanthen-1-yloxy)acetate] with an average polymer chain length of less than 5 monomer units (CAS RN #813452-37-8)	to be deleted
3824909260	N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluoroacetyl-L-lysyl-N2-carboxy anhydride in a solution of dichloromethane at 37 %	Automatisch
3824909261	3',4',5'-Trifluorobiphenyl-2-amine, in the form of a solution in toluene containing by weight 80 % or more but not more than 90 % of 3',4',5'-trifluorobiphenyl-2-amine	Automatisch
3901300080	Ethylene-vinyl acetate copolymer, — containing 27,8 % or more but not more than 29,3 % by weight of vinyl acetate — with a melt flow index of 22 g/10 min or more but no more than 28 g/10 min — containing not more than 15 mg/kg vinyl acetate monomer	Automatisch
3901300082	Ethylene-vinyl acetate copolymer, — containing 9,8 % or more but not more than 10,8 % by weight of vinyl acetate — with a melt flow index of 2,5 g/10 min or more but no more than 3,5 g/10 min — containing not more than 15 mg/kg vinyl acetate monomer	Niet automatisch
3901909080	Block copolymer of ethylene with octene in the form of pellets: — with a specific gravity of 0,862 or more, but not more than 0,865, — able to stretch to at least 200 % its original length, — with a hysteresis of 50 % (± 10 %), — with permanent deformation of not more than 20 %, for use in the manufacture of napkin liners for babies # (1)	Automatisch
3901909082	Copolymer of ethylene and methacrylic acid	Automatisch
3902100050	High isotactic polypropylene (HIPP), whether or not coloured, intended for the manufacture of plastic components for air freshener with the following properties: — a density of 0,880 g/cm ³ or more but not more than 0,913 g/cm ³ (as determined by test method ASTM D1505), — a tensile strength at yield of 350 kg/cm ² or more but not more than 390 kg/cm ² (as determined by test method ASTM D638) — a heat deflection temperature of 135 °C or more under load of 0,45 MPa (as determined by test method ASTM 648) (1)	Automatisch
3902909084	Blend of hydrogenated styrenic block copolymer, polyethylene wax, and tackifier resin, in the form of pellets, containing by weight: — 70 (± 5) % of styrenic block copolymer, — 15 (± 5) % of polyethylene wax, and — 15 (± 5) % of tackifier resin with the following physical properties: — able to stretch to at least 200 % of its original length — with a hysteresis of 50 (± 10) % — with a permanent deformation of no more than 20 % for use in the manufacture of napkins and napkin liners for babies # (1)	Niet automatisch

3903909050	Crystalline copolymer of styrene and p-methylstyrene: — with a melting point of 240 °C or more but not more than 260 °C, — containing 5 % or more but not more than 15 % by weight of p-methylstyrene	Niet automatisch
3904698081	Poly(vinylidene fluoride) (CAS RN 24937-79-9)	Automatisch
3906909040	Transparent acrylic polymer in packages of not more than 1 kg, and not for retail sale with: — a viscosity of not more than 50000 Pa•s at 120 °C as determined by the test method ASTM D 3835 — a weight average molecular weight (Mw) of more than 500 000 but not more than 1 200 000 according to the Gel Permeation Chromatography (GPC) test, — a residual monomer content of less than 1 %	Automatisch
3907201140	Polyethylene glycol with an ethylene oxide chain length of not more than 30, having butyl-2-cyano 3-(4-hydroxyphenyl) acrylate end groups, for use as a UV barrier in liquid masterbatches# (1)	Niet automatisch
3907999030, 3913900020	Poly(hydroxyalkanoate), predominantly consisting of poly(3-hydroxybutyrate)#	Automatisch
3907999080	Copolymer, consisting of 72 % by weight or more of terephthalic acid and/ or derivatives thereof and cyclohexanedimethanol, completed with linear and/ or cyclic dioles	Automatisch
3909400020	Powder of thermosetting resin in which magnetic particles have been evenly distributed, for use in the manufacture of ink for photocopiers, fax machines, printers and multifunction devices# (1)	Automatisch
3911909930	1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated	Automatisch
3911909931	Copolymers of butadiene and maleic acid, whether or not containing its ammonium salts	to be deleted
3911909935	Alternated copolymer of ethylene and maleic anhydride (EMA)	Automatisch
3912110040	Cellulose diacetate powder	Automatisch
3919108023	Reflecting film, consisting of several layers including: — poly(vinyl chloride); — polyurethane with, on one side, imprints against counterfeiting, alteration or substitution of data or duplication, and on the other side, a layer of glass microspheres; — a layer incorporating a security and/or official mark which changes appearance with angle of view; — metallised aluminium; — and adhesive, covered on one side with a release liner	to be deleted

3919108032	Polytetrafluoroethylene film: — with a thickness of 110 µm or more, — with a surface resistance of between 102-1014 ohms as determined by test method ASTM D 257, — coated on one side with an acrylic pressure sensitive adhesive	to be deleted
3919108037	Polytetrafluoroethylene film: — with a thickness of 100 µm or more, — an elongation at break of not more than 100 %, — coated on one side with a pressure sensitive silicon adhesive	to be deleted
3919108043, 3919900026	Ethylene vinyl acetate film: — of a thickness of 100 µm or more, — coated on one side with an acrylic pressure sensitive or UV-sensitive adhesive and a polyester or polypropylene liner #	Automatisch
3919900060	Reflecting film containing: — a poly(vinyl chloride) layer, — a polyurethane layer, — a glass microspheres layer, — a layer whether or not incorporating a security and/or official mark which changes appearance with angle of view, — a metallised aluminium layer, and — an adhesive, covered on one side with a release liner	Automatisch
3919900063	Co-extruded trilayer film, — each layer containing a mixture of polypropylene and polyethylene, — containing not more than 3 % by weight of other polymers, — whether or not containing titanium dioxide in the core layer, — coated with an acrylic pressure sensitive adhesive and — with a release liner — of an overall thickness of not more than 110 µm	Automatisch
3919900065	Self-adhesive film with a thickness of 40 µm or more, but not more than 400 µm, consisting of one or more layers of transparent, metallised or dyed poly(ethylene terephthalate), covered on one side with a scratch resistant coating and on the other side with a pressure sensitive adhesive and a release liner	Automatisch
3919900070	Self-adhesive polishing discs of microporous polyurethane, whether or not coated with a pad	Automatisch
3920621948	Sheets or rolls of poly(ethylene terephthalate): — coated on both sides with a layer of epoxy acrylic resin, — of a total thickness of 37 µm (± 3 µm)	Automatisch
3921905530	Prepreg sheets or rolls containing brominated epoxy resin reinforced with glass fabric, having — a flow of not more than 3,6 mm (as determined by IPC-TM 650.2.3.17.2), and — a glass transition temperature (Tg) of more than 170 °C (as determined by IPC-TM 650.2.4.25) for use in the manufacture of printed circuit boards# (1)	to be deleted

5402470020	Bicomponent monofilament yarn of not more than 30 dtex, consisting of: — a poly(ethylene terephthalate) core, and — an outer layer of a copolymer of poly(ethyleneterephthalate) and poly(ethyleneisophthalate), for use in the manufacture of filtration fabrics# (1)	Automatisch
5603131020	Non-woven of spunbonded polyethylene, with a coating, — of a weight of more than 80 g/m ² but not more than 105 g/m ² and — an air resistance (Gurley) of 8 seconds or more but not more than 75 seconds (as determined by the ISO 5636/5 method)	Automatisch
6909190020	Silicon nitride (Si ₃ N ₄) rollers or balls	Automatisch
7009910010	Unframed glass mirrors with: — a length of 1516 mm (± 1 mm); — a width of 553 mm (± 1 mm); — a thickness of 3 mm (± 0,1 mm); — the back of the mirror covered with protective polyethylene (PE) film, with a thickness of 0,11 mm or more but not more than 0,13 mm; — a lead content of not more than 90 mg/kg and — a corrosion resistance of 72 hours or more according to ISO 9227 salt spray test	Automatisch
7019191020	Yarn of 10,3 tex or more but not more than 11,9 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 µm or more but not more than 5,83 µm predominate	Automatisch
7019191025	Yarn of 5,1 tex or more but not more than 6,0 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 µm or more but not more than 5,83 µm predominate	Automatisch
7202998010	Ferro-dysprosium, containing by weight: — 78 % or more of dysprosium, and — 18 % or more but not more than 22 % of iron	Automatisch
7604291010, 7606129920	Sheets and bars of aluminium-lithium alloys#	Automatisch
7607209020	Lubricating entry sheet of a total thickness of not more than 350 µm, comprising of: — a layer of aluminium foil of a thickness of 70 µm or more but not more than 150 µm, — a water soluble lubricant of a thickness of 20 µm or more but not more than 200 µm and solid at room temperature	Niet automatisch
8104300030	Magnesium powder: — of purity by weight of 99,5 % or more, — with a particle size of 0,2 mm or more but not more than 0,8 mm	Automatisch
8108903030	Titanium-aluminium-vanadium alloy (TiAl ₆ V ₄) wire, complying with AMS standards 4928 and 4967	Automatisch

8301600010, 8413910020, 8419908520, 8438900010, 8468900010, 8476900010, 8479908087, 8481900020, 8503009945, 8515900020, 8531908520, 8536908596, 8543900050, 8708919910, 8708999730, 9031908530	Keypads, wholly of either silicone or polycarbonate, including printed keys with electrical contacting elements#####	Automatisch
8407909020	Compact Liquid Petroleum Gas (LPG) Engine System, with: — 6 cylinders, — an output of 75 kW or more, but not more than 80 kW, — inlet and exhaust valves modified to operate continuously in heavy duty applications, for use in the manufacture of vehicles of heading 8427# (1)	Automatisch
8413703520	Single phase centrifugal pump: — discharging at least 400 cm ³ fluid per minute, — with a noise level limited to 6 dBA, — with the inside diameter of the suction opening and discharge outlet of not more than 15 mm, and — working at ambient temperatures down to -10°C	Automatisch
8414592040	Axial fan with an electric motor, of an output of not more than 2 W, for use in the manufacture of products of heading 8521 or 8528 # (1)	Automatisch
8479899750, 8479908080	Machinery, being components of a production line for the manufacture of lithium ion batteries for passenger electric motor vehicles, for the construction of such a production line# (1)#	Automatisch
8483409080	Transmission gearbox, with: — not more than 3 gears, — an automatic deceleration system and — a power reversal system, for use in the manufacture of goods of heading 8427 # (1)	Automatisch

8504509540	Coil choke with: — an inductance of 4,7 μ H (\pm 20 %), — a DC resistance of not more than 0,1 Ohms, — an insulation resistance of 100 MOhms or more at 500 V (DC) for use in the manufacture of LCD and LED module power boards # (1)	Automatisch
8507102080	Lead acid starter battery, with: — a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge, — a liquid electrolyte, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator controls # (1)	Automatisch
8507600060	Lithium-ion rechargeable batteries, with: — a length of 1 213 mm or more, but not more than 1 575 mm, — a width of 245 mm or more but not more than 1 200 mm, — a height of 265 mm or more, but not more than 755 mm, — a weight of 265 kg or more but not more than 294 kg, — a nominal capacity of 66,6 Ah, put up in packs of 48 modules	Automatisch
8507600070	Rectangular modules for incorporation in lithium-ion rechargeable batteries: — of a length of 350 mm or 312 mm, — of a width of 79,8 mm or 225 mm, — of a height of 168 mm or 35 mm, — of a weight of 6,2 kg or 3,95 kg, — with a rating of 129 Ah or 66,6 Ah	Automatisch
8507600080	Rectangular lithium-ion-accumulator or module, with — a metal casing, — a length of 171 mm (\pm 3 mm), — a width of 45,5 mm (\pm 1 mm), — a height of 115 mm (\pm 1 mm), — a nominal voltage of 3,75 V and — a nominal capacity of 50 Ah for use in the manufacture of rechargeable batteries for motor vehicles# (1)	Automatisch
8508700010, 8537109996	Electronic circuit card without separate housing for actuating and controlling vacuum cleaner brushes powered by not more than 300 W#	Automatisch
8508700020, 8537109998	Electronic circuit cards that: — are connected by wire or radio frequency to each other and the motor controller card, and — regulate the functioning (switching on or off and suction capacity) of vacuum cleaners according to a stored program, — whether or not fitted with indicators that display the functioning of the vacuum cleaner (suction capacity and/or dust bag full and/or filter full) #	Automatisch
8518408092	Circuit board sub-assembly, comprising power supply, active equalizer and power amplifier circuits	Automatisch

8526912080, 8527290010	Integrated audio module (IAM) with a digital video output for connection to an LCD touch screen monitor, interfaced over the Media Oriented Systems Transport (MOST) network and transported over the MOST High protocol, with or without — a printed circuit board (PCB) containing a Global Positioning System (GPS) receiver, a gyroscope, and a Traffic Message Channel (TMC) tuner, — a hard disk drive supporting multiple maps, — a HD radio, — a voice recognition system, — a CD and DVD drive, and including — Bluetooth, MP3 and USB input connectivity, — a voltage of 10 V or more but not more than 16 V, for the use in the manufacture of vehicles in Chapter 87# (1)#	deleted due to obj
8529906565	Printed circuit board for distributing supply voltage and control signals directly to a control circuit on a TFT glass panel of a LCD module	Automatisch
8529909225	LCD modules, not combined with touch screen facilities, solely consisting of: — one or more TFT glass or plastic cells, — a die cast heat sink, — a backlight unit, — one printed circuit board with micro controller, and — LVDS (Low Voltage Differential Signalling) interface, for use in the manufacture of radios for motor vehicles # (1)	Automatisch
8529909250	Colour LCD display panel for LCD monitors of heading 8528: — with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm, — with backlight, micro-controller, — with a CAN (Controller area network)-controller with LVDS (Low-voltage differential signalling) interface and CAN/power supply socket or with an APIX (Automotive Pixel Link) controller with APIX interface, — in a housing with or without a heat sink at the back of the housing, — without a signal-processing module, for use in the manufacture of vehicles of chapter 87# (1)	Automatisch
8535900030, 8536508083	Semiconductor module switch in a casing: — consisting of an IGBT transistor chip and a diode chip on one or more lead frames, — for a voltage of 600 V or 1 200 V #	Automatisch
8536699084	Universal serial bus (USB) socket or plug in a single or multiple form for connecting with other USB devices, for use in the manufacture of goods falling within headings 8521 or 8528# (1)	Automatisch
8537109997	Electronic controller card for actuating and controlling of a single-phase electric AC commutator motor, with an output of 750 W or more and an input power of more than 1 600 W but not more than 2 700 W	Niet automatisch
8543709040	High-frequency amplifier comprising one or more integrated circuits and discrete capacitor chips on a metal flange in a housing	Automatisch

8543709095	Mobile telephone view and control module comprising of: — a mains power/ CAN (Controller area network) output socket, — a universal serial bus (USB) and audio IN/OUT ports and — incorporating a video switching device for the interface of smart phone operating systems with the Media Orientated Systems Transport network (MOST), for use in the manufacture of vehicles of Chapter 87 # (1)	Automatisch
8545909020	Carbon fibre paper of a kind used for gas diffusion layers in fuel cell electrodes	Automatisch
8708309110	Drum type parking brake: — operating within the service brake disk, — with a diameter of 170 mm or more but not more than 175 mm, for use in the manufacture of motor vehicles# (1)	Automatisch
9001900085	Light guide panel made of poly(methyl methacrylate): — whether or not cut, — whether or not printed, for use in the manufacture of backlight units for flat screen TVs# (1)	Automatisch
9401908010	Ratchet disk of a kind used in the manufacture of reclining car seats	Automatisch
9405403980, 9405409907	Ambient light LED board to be incorporated in goods of heading 8528 # (1)#	Niet automatisch
9503007510, 9503009510	Plastic cable car scale models, whether or not with a motor, for printing (1)#	Automatisch